



Guiberson Type “T-60” Tubing Spider

This tubing spider is a pneumatically operated unit rated at 60 tons, designed for fast, safe, and dependable one-man operation. It easily handles up to 25,000 ft of 2-3/8 in. O.D. tubing, converts quickly from manual to air operation, and accommodates pipe sizes from 1.315 in. to 4-1/2 in. O.D. Its positive-rotation grip ensures automatic alignment, even load distribution, maximum holding power, and instant release, while the guard gate protects slips and linkage and the plain gate design minimizes clearance issues.

| MODEL CAPACITY | T-60 60000 LBS (5431 KG) | WEIGHT LBS (KG) |
|------------------------------------|--|---------------------------------|
| Tubing Spider Assembly | 50684 (w/o slip) 67580 (w/ 2-7/8" slip) 62458 (w/ 3-1/2" slip) | 155 (70) 190 (86) 191(87) |
| Slip Body Assembly, 2-7/8" Nominal | 62461 | 35 (15.9) |
| Slip Insert Set, 2-7/8" Nominal | | |
| 1.050" (26.7 mm) Tubing | 62473 | 17 (7.71) |
| 1.315" (33.4 mm) Tubing | 62474 | 14 (6.35) |
| 1.660" (42.1 mm) Tubing | 62475 | 12 (5.44) |
| 1.900" (48.2 mm) Tubing | 62476 | 11 (5.00) |
| 2.060" (52.3 mm) Tubing | 62478 | 10 (4.54) |
| 2-3/8" (60.3 mm) Tubing | 42586-18 | 9 (4.08) |
| 2-7/8" (73.0 mm) Tubing | 42587-18 | 7 (3.18) |
| Slip Body Assembly, 3-1/2" Nominal | 62462 | 36 (16.3) |
| Slip Inserts Set, 3-1/2' Nominal | | |
| 1.315" (33.4 mm) Tubing | N/A | 21 (9.53) |
| 1.660" (42.1 mm) Tubing | N/A | 17 (7.71) |
| 1.900" (48.2 mm) Tubing | N/A | 16 (7.26) |
| 2.060* (52.3 mm) Tubing | N/A | 14 (6.35) |
| 2-3/8" (60.3 mm) Tubing | N/A | 12 (5.44) |
| 2-7/8" (73.0 mm) Tubing | N/A | 11 (5.00) |
| 3-1/2" (88.9 mm) Tubing | 42588-18 | 9 (4.08) |
| Slip Body Assembly, 4" Nominal | 49933 (INTEGRAL) | 50 (22.7) |
| Slip Body Assembly, 4-1/2" Nominal | 34989 (INTEGRAL) | 45 (20.4) |
| Slip Insert Set, 4-1/2" Nominal | | |
| 3-1/2" (88.9 mm) Tubing | N/A | 24 (10.89) |
| 4" (101.6 mm) Tubing | N/A | 18 (8.16) |
| | N/A | 9 (4.08) |