


DCS Drill Collar Slips

MOT drill collar slips provide superior holding power. Each slip segment is a rugged drop forging, with an extra long back to provide maximum support to the circular button gripping elements. Full wraparound design and circular buttons assure positive holding and slip setting. Drill collar slips are flat on top to accommodate the MP Clamp. All Varco slips have an API taper of 4 in./ft on the diameter.

DCS- Multi Segment Drill Collar Slips

Slip Type	DCS-S		DCS-R		DCS-L					
	3 - 4	4 - 4-7/8	4-1/2 - 6	5-1/2 - 7	6-3/4 - 8-1/4	8 - 9-1/2	8-1/2 - 10	9-1/4 - 11-1/4*	11 - 12-3/4*	12 - 14*
P/N, Slip complete	2572	2573	2552	2550	2503	2507	2530	2508	2534	2636
Weight, complete lbs (kg)	112 (51)	103 (47)	120 (54)	112 (51)	154 (70)	173 (78)	185 (84)	198 (90)	213 (96.5)	207 (94)
Total Segments	7	7	9	9	11	12	13	14	17	17
Total Hinge Pins	6	6	8	8	10	11	12	13	16	16
Use in Insert Bowl	No. 3 Regular or Extended					No.3 Ext.	No. 2		No. 1	

***This size is furnished with four handles**

Circular Buttons for DCS Slips

Circular Buttons				
Slip Set	Drill Collar OD (in.)	P/N	Weight lbs (kg)	Qty
DCS-S	3-4	2828 - 49	13 (6)	49
	4 - 4-7/8	2620 - 49	8 (3.5)	49
DCS-R	4-1/2 - 6	2628 - 63	16 (7)	63
	5-1/2 - 7	2620 - 63	11 (5)	63
DCS-L	5-1/2 - 7	2513 - 88	22 (10)	88
	6-3/4 - 8-1/4	2630 - 88	15 (7)	88
	8 - 9-1/2	2630 - 96	16 (7)	96
	8-1/2 - 10	2627 - 104	26 (12)	104
	9-1/4 - 11-1/4	2630 - 112	19 (8.5)	112
	11 - 12-3/4	2625 - 136	13(6)	136
	12 - 14	2630 - 136	16(7)	136

Part List

Slip Type	DCS-S		DCS-R		DCS-L	
	P/N	Weight lbs (kg)	P/N	Weight lbs (kg)	P/N	Weight lbs (kg)
Segment—Right End	2568	11 (5)	2554	10 (4.5)	2510	12 (5.5)
Segment—Left End	2569	11 (5)	2555	10 (4.5)	2511	12 (5.5)
Segment—Intermediate	2570	11 (5)	2556	10 (4.5)	2512	12(5.5)
Hinge Pin w/Cotter Pin	2525	.5 (0.2)	2525	.5 (0.2)	2520	.7 (0.3)
Handle Pin w/Washer & Cotter Pin	3769	.5 (0.2)	3769	.5 (0.2)	3769	.5 (0.2)
Handle- Right & Left End Segment	3765	3.5 (1.5)	3765	3.5 (1.5)	3765	3.5 (1.5)
Handle for Intermediate Segments	3766	4 (2)	3766	4 (2)	3766	4(2)
Retaining Cotter Pin	71936	—	71936		71936	