



SUCKER ROD HOOK
MODEL: RH-25S



SUCKER ROD HOOK
MODEL: RH-25L



SUCKER ROD HOOK
MODEL: RH-35



SUCKER ROD HOOKS			
MODEL	RATED CAPACITY (u.s tons)	LENGTH (in./mm)	WEIGHT (lbs./kg)
RH-25S	25	$\frac{20}{494}$	$\frac{48}{22}$
RH-25L	25	$\frac{31}{798}$	$\frac{99}{45}$
RH-35	35	$\frac{38}{960}$	$\frac{119}{54}$
REPAIR KITS			
RH-25SRK	25 Ton Repair Kit Includes: 1 Spring Housing, 1 Latch, 1 Lever, 1 Lever Pin, 1 Latch Pin, 1 Spring		$\frac{11}{5}$
RH-25LRK	35 Ton Repair Kit Includes: 1 Latch, 1 Latch Handle, 1 Latch Spring, 2 Roll Pins, 1 Comp. Spring, 1 Clevis Pin		$\frac{18}{8}$
RH-35SRK	35 Ton Repair Kit (Includes: 1 Latch, 1 Latch Handle, 1 Latch Spring, 2 Roll Pins, 1 Comp. Spring, 1 Clevis Pin		$\frac{22}{10}$

MOT&S Sucker Rod Hooks

Are designed and manufactured according to API Spec 8A/8C Specifications for Drilling and Well Servicing hoisting equipment. They are suitable for all depths and operating conditions.

FEATURES:

- Designed for 25 Ton and 35 Ton load ratings.
- Choice of Short and Long Models.
- Special design snap-in latch mechanism permits elevator bail to hook in without operator releasing latch, and held secure until released.