



Type **MYT** is a light-weight (195 Lb) elevator for medium wells. It handles all tubing within its range with one set of slips, plus reducing inserts. The MYT has four curved slips that form a circle around the tubing. This assures a uniform grip with minimum marking of pipe.

**TYPE MYT SLIP
TUBING ELEVATOR
MODEL: MYT- 40 Ton**



SPECIFICATIONS: TYPE MYT CENTER LATCH SLIP TUBING ELEVATOR					
PART NAME:	RANGE	PART NO.	WELDLESS LINKS	RATED CAPACITY	WEIGHT DRESSED (APPROX.)
TYPE MYT	1.315" - 2-7/8"	29328	1-1/4" - 2-3/4"	40 TON	195 LBS
SIZE	SLIP ASSEMBLY	INSERT	INSERT QTY	SETTING RING	
2-7/8" X 1" (1.315")	29343-7	29259	8	29354	
2-7/8" X 1-1/4" (1.660")	29343-6	29258	8	29353	
2-7/8" X 1-1/2" (1.900")	29343-5	29257	8	29352	
2-7/8" X 2.000"	29343-4	29256	8	29351	
2-7/8" X 2-1/16"	29343-3	29256	8	29350	
2-7/8" X 2-3/8"	29343-2	29255	8	29345	
2-7/8" X 2-7/8"	29343-1	24773	8	29348	

The **YT** is an outstanding combination tool for use with any of the power tubing spiders. It has four slips each contacting 9 inches of pipe length. The interlocking slips form a circle around the tubing, assuring a uniform grip. Slip inserts are easily replaceable. Only one set of slip body is required to handle all tubing sizes from 1.315 through 2-7/8". A sturdy latch and safety latch-lock combination holds the YT securely in closed position.

**TYPE YT SLIP
TUBING ELEVATOR
MODEL: YT - 75 TON**



SPECIFICATIONS: TYPE YT CENTER LATCH SLIP TUBING ELEVATOR					
PART NAME:	RANGE	PART NO.	WELDLESS LINKS	RATED CAPACITY	WEIGHT DRESSED (APPROX.)
TYPE YT	1.315" - 3-1/2"	23105-3	2-1/4" - 2-3/4"	75 TON	450 LBS
SIZE	SLIP ASSEMBLY	INSERT	INSERT QTY	SETTING RING	
2-7/8" X 1" (1.315")	23108-11	29259	12	29001	
2-7/8" X 1-1/4" (1.660")	23108-10	29258	12	27810	
2-7/8" X 1-1/2" (1.900")	23108-9	29257	12	27811	
2-7/8" X 2"	23108-8	29256	12	27821	
2-7/8" X 2-1/16"	23108-7	29256	12	27812	
2-7/8" X 2-3/8"	23108-6	29255	12	27694	
2-7/8" X 2-7/8"	23108-4	24773	12	27695	
3-1/2" X 2-7/8"	23108-3	30358	12	27695	
3-1/2" X 3-1/2"	23108-5	24774	12	27813	



The **HYT** is designed to accommodate the widest possible range of tubing. The key is the various combinations possible with three different slip-setting rings, reducing inserts and two sizes of slips. The HYT handles 2-3/8", 2-7/8" or 3-1/2" OD tubing, with any type of upset and any wall thickness.

**TYPE HYT SLIP
TUBING ELEVATOR
MODEL: HYT - 150 Ton**



SPECIFICATIONS: TYPE HYT CENTER LATCH SLIP TUBING ELEVATOR					
PART NAME:	RANGE	PART NO.	WELDLESS LINKS	RATED CAPACITY	WEIGHT DRESSED (APPROX.)
TYPEHYT	2-3/8" - 3-1/2"	39284	2-1/4" - 3-1/2"	150 TON	900 LBS
SIZE	SLIP ASSEMBLY	INSERT	INSERT QTY	SETTING RING	
2-7/8" X 2-3/8"	39259-4	29255	16	39214-1	
2-7/8" X 2-7/8"	39259-2	24773	16	39214-2	
3-1/2" X 2-7/8"	39258-4	30358	32	39214-2	
3-1/2" X 3-1/2"	39258-2	24774	32	39214-3	

The **HYC** elevator is the newest in the series of Type "Y" series elevators. It provides 200 Ton capacity and can handle from 3-1/2" to 7-3/4" tubing or casing. The full range can be achieved with the use of three sets of slips. All slips provide a full 10-1/2" of insert contact to firmly grip your casing or tubing. The HYC elevator as with all Type 'Y' series elevators operate with the latch-lock combination for safety. When your 250 ton elevator/spiders are more than you need, and your 75 ton slip type elevator is not enough, remember the 200 ton HYC elevator.

**TYPE HYC SLIP
CASING TUBING ELEVATOR
MODEL: HYC- 200 TON**



SPECIFICATIONS: TYPE HYC CASING - TUBING ELEVATOR					
PART NAME:	RANGE	PART NO.	WELDLESS LINKS	RATED CAPACITY	WEIGHT DRESSED (APPROX.)
TYPEHYC	3-1/2" - 7-3/4"	55310	2-1/4" - 3-1/2"	200 TON	1200LBS
SIZE	SLIP ASSEMBLY	INSERT	INSERT QTY	SETTING RING	GUIDE PLATE
4-1/2" X 3-1/2"	55509	24779	24	55516	26827-1
4-1/2" X 4"	55510	24781	24	55517	26827
4-1/2" X 4-1/2"	55511	16408	24	55518	24071-4
5-1/2" X 5"	55512	24783	36	55519	24071
5-1/2" X 5-1/2"	55513	16407	36	55520	24701-1
7" X 6-5/8"	55514	24748	48	55521	24701-3
7" X 7"	55515	16407	48	55522	24701-2
7-5/8" X 7-5/8"	70009	16407	48	70012	24701-6
7-5/8" X 7-3/4"	70015	32477	48	70014	24701-6